

**PRODUCT REQUIREMENT SHEET**

See LV 75-032

<b>MEASURING VOLTAGE</b>	230V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Horizontal
<b>BURNING POSITION</b>	P15
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

	VALUE UNIT	TOLERANCE
<b>WATTAGE</b>	300W	± 5 %
<b>LIFE</b>	1000 h	average
<b>COLOR TEMPERATURE</b> Clear lamp Lamp with reflector	2500 K NA	indicative
<b>FLUX</b>	2250 lm 1980 Lm	Nominal Mini
<b>WEIGHT</b>	11 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9238 503 43300			01/03/2011				
9238 503 43300		INFRARED INDUSTRIAL						0833/000							
0833/000 p. 190-2		13908R CL 230V 300W R7s													
Of 04/02/2002		REF. : PDM IRK 2010-053		DOCUMENTATION	UNIT mm	PROJ EUROP	2	SH	SH	190-2	10		A4		
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															