

**PRODUCT REQUIREMENT SHEET**

See LV 75-032

<b>MEASURING VOLTAGE</b>	235V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Vertical
<b>BURNING POSITION</b>	Any
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

	VALUE UNIT	TOLERANCE
<b>WATTAGE</b>	3000W	± 6 %
<b>LIFE</b>	5000 h	average
<b>COLOR TEMPERATURE</b> Clear lamp Lamp with reflector	2500 K NA	± 100 K
<b>FLUX (HeLeN lamp)</b>	NA	
<b>WEIGHT</b>	80 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 143 44500			26/01/2011				
9245 143 44500		INFRARED INDUSTRIAL STANDARD						0833/000							
0833/000 p. 190-2		13565V 3000W 220-250V CL													
Of 20/10/2003		REF. : PDM IRK 2010-082		DOCUMENTATION	UNIT mm	PROJ EUROP	2	SH	SH	190-2	10		A4		
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															