


**PRODUCT REQUIREMENT SHEET**

See LV 75-32

<b>MEASURING VOLTAGE</b>	240V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Horizontal
<b>BURNING POSITION</b>	P15
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

		VALUE UNIT	TOLERANCE
<b>WATTAGE</b>		1000W	± 6 %
<b>LIFE</b>		5000 h	average
<b>COLOR TEMPERATURE</b>	Clear lamp	2500 K	± 100 K
	Lamp with reflector	NA	
<b>FLUX (HeLeN lamp)</b>	Clear lamp	NA	
	Reduction	NA	
<b>WEIGHT</b>		30 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP INFRARED INDUSTRIAL STANDARD 1000T3 1000W 240V CL								9245 179 45500			29/03/2013		
New										0833/000					
REF. :	CRP 1309	DOCUMENTATION	UNIT mm		2	SH	SH	190-2	10					A4	
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD					DR. FISCHER Europe								
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															