

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	600V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

		VALUE UNIT	TOLERANCE
WATTAGE		2500W	± 6 %
LIFE		5000 h	average
COLOR TEMPERATURE	Clear lamp	2500 K	± 100 K
	Lamp with reflector	NA	
FLUX (HeLeN lamp)	Clear lamp	NA	
	Reduction	NA	
WEIGHT		82 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 291 51200		04/07/2013					
9245 291 51200		INFRARED INDUSTRIAL						0833/000							
0833/000 p. 190-2		13848/99 2500W 600V CL													
Of 21/11/2003		REF. : PDM IRK 2010-053		DOCUMENTATION		UNIT mm	PROJ EUROP	2	SH	SH	190-2	10		A4	
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															