

**PRODUCT REQUIREMENT SHEET**

See LV 75-032

<b>MEASURING VOLTAGE</b>	400V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Horizontal
<b>BURNING POSITION</b>	P15
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

		VALUE UNIT	TOLERANCE
<b>WATTAGE</b>		2500W	± 6 %
<b>LIFE</b>		5000 h	average
<b>COLOR TEMPERATURE</b>	Clear lamp	2650 K	± 100 K
	Lamp with reflector	2550 K	Indicative value
<b>FLUX (HeLeN lamp)</b>	Clear lamp	NA	
	Reduction	NA	
<b>WEIGHT</b>		61 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 547 49100			03/04/2012				
9245 547 49100		INFRARED INDUSTRIAL						0833/000							
0833/000 p. 190-2		14140C/98 2500W 400V REFL													
Of 05/11/2010		REF. : PDM IRK 2011-031		DOCUMENTATION		UNIT	mm	PROJ EUROPE	2	SH	SH	190-2	10		A4
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD				DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															