

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	400V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	3000W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2650 K 2550 K	± 100 K Indicative value
FLUX (HeLeN lamp) Clear lamp Reduction	NA NA	
MAXIMUM IRRADIANCE LEVEL AT 10 CM	15000 W/m ²	Min
WEIGHT	62 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 628 49100			05/02/2016				
9245 628 49100		INFRARED INDUSTRIAL						0833/000							
0833/000 p. 190-2		14156C/83 3000W 400V REFL													
Of 03/04/2012		REF. : CRP 1549		DOCUMENTATION		UNIT mm	PROJ EUROP	2	SH	SH	190-2	10		A4	
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															