


PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	575V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	2500W	± 150W
LIFE	5000 h	average
COLOR TEMPERATURE	Clear lamp Lamp with reflector	2500 K NA ± 100 K
FLUX (HeLeN lamp)	Clear lamp Reduction	NA NA
WEIGHT	66 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES : 9245 705 51500 0833/000 p. 190-2 Of 27/05/2004		HALOGEN LAMP INFRARED INDUSTRIAL 14168C 2500W 575V CL						9245 705 51500 0833/000			04/07/2013				
REF. :	PDM IRK 2010-053	DOCUMENTATION	UNIT mm		2	SH	SH	190-2	10				A4		
NOM :	J.P. CHARLIER	VALIDATION : A. PICHARD				DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															