

PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Vertical
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	2500W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE	Clear lamp Lamp with reflector	2450 K NA
FLUX (HeLeN lamp)	Clear lamp Reduction	NA NA
WEIGHT	43 g	

Project

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 800 44900			24/01/2014				
9245 800 44900		INFRARED INDUSTRIAL						0833/000							
0833/000 p. 190-2		14190V 2500W 235V CL													
Of 28/01/2008		REF. : CRP 1405		DOCUMENTATION	UNIT mm	PROJ EUROP	2 SH	SH	190-2	10			A4		
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															