


PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	230V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Vertical
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	300W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2550 K * NA	Indicative value *
IRRADIANCE LEVEL	3400 W/m ²	mini
WEIGHT	9.7 g	

Project

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 915 44200			29/01/2015				
9245 915 44200		INFRARED INDUSTRIAL REFLECTOR						0833/000							
0833/000 p.190-2		13908R/83 300W 230V													
Of 09/07/2013		REF. : PDM IRK 2014-053		DOCUMENTATION		UNIT	PROJ EUROP	2	SH	SH	190-2	10	A4		
						mm									
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															