

**PRODUCT REQUIREMENT SHEET**

See LV 75-32

<b>MEASURING VOLTAGE</b>	230V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Vertical *
<b>BURNING POSITION</b>	Any *
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

	VALUE UNIT	TOLERANCE	
<b>WATTAGE</b>	300W	± 6 %	
<b>LIFE</b>	2000 h *	average	
<b>COLOR TEMPERATURE</b>	Clear lamp Lamp with reflector	2550 K NA	Indicative value
<b>FLUX (HeLeN lamp)</b>	Clear lamp Reduction	NA NA	
<b>WEIGHT</b>	32 g		

Project

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 921 44200			19/08/2015				
9245 921 44200		INFRARED CLEAR SLEEVE						0833/000							
0833/000 p.190-2		13908J 300W 230V													
Of 29/01/2015		REF. : PDM IRK 2015-011		DOCUMENTATION		UNIT	mm	PROJ EUROP	2	SH	SH	190-2	10		A4
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															