



Finish : Clear

1	0833	2	0833	3	0000	4		5		6		7		8
SUPERSEDES 9245 548 31900 0833/000 p.190-1 Of 25/10/2004				HALOGEN LAMP INFRARED INDUSTRIAL 13296C2 400W 110V CL						9245 548 31900 0833/000			19/09/2011	
REF. : PDM IRK 2010-053		DOCUMENTATION		UNIT mm	PROJ. EUROP 	2 SH		SH 190-1	10	SCA. 1	A4			
NAME : J.P. CHARLIER		VALIDATION : A. PICHARD			DR. FISCHER Europe									
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.														

PRODUCT REQUIREMENT SHEET

See LV 75-032

MEASURING VOLTAGE	110V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal
BURNING POSITION	P4
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE	
WATTAGE	400W	± 6 %	
LIFE	5000 h 3750 h	Average Mini	
COLOR TEMPERATURE	Clear lamp Lamp with reflector	1800 K NA	± 100 K
FLUX (HeLeN lamp)	Clear lamp Reduction	NA NA	
WEIGHT	43 g		

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 548 31900			19/09/2011				
9245 548 31900		INFRARED INDUSTRIAL						0833/000							
0833/000 p. 190-2		13296C2 400W 110V CL													
Of 25/10/2004		REF. : PDM IRK 2010-053		DOCUMENTATION		UNIT mm	PROJ EUROP	2	SH	SH	190-2	10		A4	
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															