



A (1 : 1)

Finish : Reflector

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES 9238 960 44500 0833/000 p. 190-1 Of 15/04/2002		HALOGEN LAMP INFRARED INDUSTRIAL 13713X/98 REFL 220-250V 1000W				9238 960 44500 0833/000			30/11/2010						
REF. : IRK N 2009-066		DOCUMENTATION		UNIT mm	PROJ. EUROP 	2 SH		SH 190-1	10	1:2	A4				
NAME : J.P. CHARLIER		VALIDATION : A. PICHARD			DR. FISCHER Europe										
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															

PRODUCT REQUIREMENT SHEET

See LV 75-032

MEASURING VOLTAGE	235V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Vertical
BURNING POSITION	Any
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	1000W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2500 K 2400 K	± 100 K Indicative value
FLUX (HeLeN lamp)	NA	
WEIGHT	34 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9238 960 44500			01/12/2010				
9238 960 44500		INFRARED INDUSTRIAL						0833/000							
0833/000 p. 190-2		13713X/98 REFL 220-250V 1000W X													
Of 15/10/2001		REF. : IRK N 2009-066		DOCUMENTATION	UNIT mm	PROJ EUROP	2	SH	SH	190-2	10		A4		
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															